



M-200 Series

High flow, Adjustable flow switch with right-angle flow

Features


- Field adjustable - Infinite flow range
- High Repeatability
- Extremely sensitive
- Minimum pressure drop
- Position Insensitive

Description

The M-200 Series flow switches are engineered and field tested for sensing increasing and decreasing flow rates of gases or liquids. Pressure variation effects are minimal. This series features such versatility, economy, and accuracy that they can be used in virtually any application requiring fool-proof inexpensive flow detection.

Operation

The flow switch is activated by flow forcing a piston kept in place by a spring to travel past a reed switch. This provides a positive signal after a certain amount of travel. Set point adjustment is controlled by adjusting the positioning of the reed switch.



Illustrated is the M-200-B Model
with 1/2" ports.

Applications

- Cleaning Tools in the semiconductor industry
- Cooling systems
- Water treatment systems
- Process flows

Measurement Specifications

Calibration Range *	3/8", 1/2", SAE8: Air : 1 - 50 scfm Water : 0.03 - 5 gpm 3/4": Air : 2 - 100 scfm Water : 0.2 - 10 gpm * Maximum flows through switch are higher. For higher flow settings, contact factory.
Set Point Accuracy	±10% maximum
Repeatability	± 2%
Hysteresis	30%
Material Versions *	<ul style="list-style-type: none"> • Acrylic • Alumunium • Brass • 316 Stainless Steel • PTFE * Other materials available on request.
Port Sizes	<ul style="list-style-type: none"> • 3/8" FNPT • 3/4" FNPT • 1/2" FNPT • SAE8

Custom Versions Available

Malema welcomes the opportunity to apply its flow sensor experience to work for its customers. Please contact the factory for any special requirements; such as ports, extreme temperature and pressure capabilities, etc.

Design Considerations/Construction

The M-100 Series comprises a Body, Piston, Endplugs, O-ring seals, and adjustment mechanism. Selecting a Flow Switch begins with selecting the body; this series is available in a number of materials. Adjustability is achieved by means of an adjustment screw controlling a bypass. Construction of the piston is important from a design perspective. We manufacture three (it is critical to select the correct piston for your application): 316 Stainless Steel, Teflon Encapsulated, and Special All-Metal piston.

(1) The standard piston is a 316 Stainless Steel piston with **epoxy** to hold the magnet in place. This piston is recommended for non-aggressive fluids and inert gases. Stainless Steel retaining rings are typically used with this piston type.

(2) The second piston that is available is a Teflon Encapsulated one. This piston is a magnet that has Teflon molded around it and then machined to the appropriate configuration. These pistons are primarily used in Teflon flow switches and also in other flow switch bodies (typically 316SS and Acrylic bodies) where customers prefer a piston that does not have epoxy in the fluid path; as well as a piston that is impervious to aggressive fluids and gases. This piston is highly recommended for medical applications. Hysteresis on these pistons does tend to be slightly higher (10 to 15%) than metal pistons due to frictional effects, weight, and surface adhesion considerations. Prior to selecting this piston, fluid temperatures and fluid compatibility with Teflon must be taken into account because certain aggressive chemicals at specific temperatures tend to swell Teflon causing the piston to change shape resulting in failure of the product. Stainless or PTFE-coated retaining rings can be used with this piston, along with a stainless spring (also coated).

(3) The third piston that is available is a Special All-Metal piston with **no epoxy** (only available in 316SS). This piston is fabricated in a proprietary process with only one weld seam (leak tested) which presents an all 316SS surface to the fluid path. This piston is recommended for those applications where the piston could experience a lot of cycling wear. This piston has been tested to 250,000 cycles at 125 psi. Stainless Steel retaining rings are recommended for this piston type.

Corporate Headquarters
 1060 S Rogers Circle
 Boca Raton, FL 33487
 P: (561) 995-0595 F: (561) 995-0622

West Coast Headquarters
 2225 Martin Avenue Suite I
 Santa Clara, CA 95050
 P: (408) 970-3419 F: (408) 970-3426

Asia Headquarters
 29 Woodlands Industrial Park E1 Northtech Unit #
 02-06 Singapore 757716
 P: (65) 6482-3533 F: (65) 6484-4231

Standard Specifications by Materials

Housing	Acrylic	Brass	316SS	PTFE
Piston*	PTFE	PTFE	PTFE	PTFE Encapsulated
Spring	Stainless Steel			PTFE Coated Stainless Steel
Retaining Ring*	Stainless Steel			PTFE Coated Stainless Steel
Pressure and Temperature Specifications				
Maximum Operating (psig)	200			
Burst (psig)	400	1,500	3,000	200
Maximum Operating Temperature	77 C (170°F)	3,000	5,000	600
		149 C (300°F)	149 C (300°F)	149 C (300°F)
Reed Switch Data (Electrical Ratings) Reed Switch	10 Watts SPST or 3 Watts SPDT (Hermetically Sealed) UL Recognized. File E47258. Operating Temperature -40°C to 125°C			
Switching Voltage	200 VDC (170 VDC for SPDT)			
Breakdown Voltage	250 VDC (200 VDC for SPDT)			
DC Resistive	10 Watts (3 Watts for SPDT)			
AC Resistive	10 VA (3VA for SPDT)			
Switching Current	0.5 A (0.25 A for SPDT)			
	1.2 A (0.5A for SPDT)			
Lead Wires	No. 24 to 18 AWG. 18" Length, Polymeric UL Recognized or Belden cable with connectors to suit			
Lead Wires Color	SPST: 2 Blue wires; SPDT: Green - Common, Yellow - Normally Closed, Orange - Normally Open			
Flow Calibration	(Higher accuracy units available)			
Set Point Accuracy	10% maximum			
Set Point Differential (Deadband)	30% (lower hysteresis on request)			
Repeatability	± 2% maximum			

* See "Design Considerations/Construction" above

Reed Switch Ratings as Recognized by UL

SPST	120 V ac 24 V dc 50V dc	0.1 A general purpose 0.25 A resistive 0.25 A resistive
SPDT	120 V ac 10 V dc 24 V dc	0.1 A general purpose 0.25 A resistive 0.1 A resistive

Corporate Headquarters
1060 S Rogers Circle
Boca Raton, FL 33487
P: (561) 995-0595 F: (561) 995-0622

West Coast Headquarters
2225 Martin Avenue Suite I
Santa Clara, CA 95050
P: (408) 970-3419 F: (408) 970-3426

Asia Headquarters
29 Woodlands Industrial Park E1 Northtech Unit #
02-06 Singapore 757716
P: (65) 6482-3533 F: (65) 6484-4231

Installation & Maintenance

This product can be mounted in any orientation. Adequate filtration and sealing procedures should be used when mounting in flow lines. For detailed directions, please refer to our "Installation and Maintenance" sheet.

Certifications

UL and Canadian UL

UL and Canadian UL Recognized for ordinary locations. File E138467


CE Compliance

Meet the intent of Directive 89/336/EEC for Electromagnetic Compatibility and Low Voltage Directive 73/23/EEC for Product Safety. Compliance was demonstrated to the following specifications as listed in the Official Journal of the European Communities: EMC Directive 89/336/EEC: EN 55011, Class B Radiated Emissions, EN 50082-1 (Immunity); IEC 801-2, Electrostatic Discharge Immunity, IEC 801-3, RF Electromagnetic Field Immunity; Low Voltage Directive 73/23/EEC: EN 61010-1, Safety Requirements for electrical equipment for measurement, control, and laboratory use.

Cv

Cv values available upon request.

Dimensional and Cut-Away Drawings






Corporate Headquarters
1060 S Rogers Circle
Boca Raton, FL 33487
P: (561) 995-0595 F: (561) 995-0622

West Coast Headquarters
2225 Martin Avenue Suite I
Santa Clara, CA 95050
P: (408) 970-3419 F: (408) 970-3426

Asia Headquarters
29 Woodlands Industrial Park E1 Northtech Unit #
02-06 Singapore 757716
P: (65) 6482-3533 F: (65) 6484-4231



Dimensional and Cut-Away Drawings (continued)

Illustrated is the M-200 Model with 1/2" ports.



Housing	A	B
Acrylic	1.25"	0.625"
Aluminum	1"	0.500"
Brass	1"	0.500"
316SS	1"	0.500"
Teflon	1.25"	0.625"

Illustrated is the M-200 Model with 3/4" ports.



* Note: The M-200 Model with 3/4" ports is only available in Brass, PTFE and 316 SS


Teflon®, Kalrez® and Viton® are registered trademarks of DuPont.

Corporate Headquarters
1060 S Rogers Circle
Boca Raton, FL 33487
P: (561) 995-0595 F: (561) 995-0622

West Coast Headquarters
2225 Martin Avenue Suite I
Santa Clara, CA 95050
P: (408) 970-3419 F: (408) 970-3426

Asia Headquarters
29 Woodlands Industrial Park E1 Northtech Unit #
02-06 Singapore 757716
P: (65) 6482-3533 F: (65) 6484-4231

Dimensional and Cut-Away Drawings (continued)



Factory Preset Information

The M-200 is an adjustable flow switch. The flow set point can be set at the factory, upon request. Proper calibration of the set point requires the following information. When purchasing a flow switch that needs to be factory preset, use the "Set Point Calibration" form on page i-vi or provide this information on the purchase order.

- Calibration set point,
- Increasing or decreasing flow,
- Fluid type (i.e. liquid or gas),
- Density or specific gravity,
- Viscosity,
- System pressure and temperature,
- Flow direction (i.e. upward or downward), and
- Mounting orientation (i.e. horizontal or vertical).

Ordering Information

Standard Part Numbering						
M	-	Model	-	Material	Port	Switch
M	-	200	-	S	1	1
		200		A - Aluminum	3 - 3/8"	1 - SPST N.O.
				B - Brass	4 - 1/2"	3 - SPDT
				P - Acrylic	6-3/4"	
				S - 316 Stainless		
				T - PTFE		

* The M-200 with 3/4" ports is ONLY available in the Brass, PTFE or 316 SS body material.
The M-200 in Brass or 316 Stainless Steel is also available with SAE 8 ports.

Corporate Headquarters
1060 S Rogers Circle
Boca Raton, FL 33487
P: (561) 995-0595 F: (561) 995-0622

West Coast Headquarters
2225 Martin Avenue Suite I
Santa Clara, CA 95050
P: (408) 970-3419 F: (408) 970-3426

Asia Headquarters
29 Woodlands Industrial Park E1 Northtech Unit #
02-06 Singapore 757716
P: (65) 6482-3533 F: (65) 6484-4231